



RHINO STAT 400

Clear Moisture Barrier

- Clear nylon low density polyethylene
- Coextruded blown film of nylon/LLDPE
- Combines excellent optics with outstanding heat and grease resistance
- Excellent seal strength and heat sealability
- Ideal for packaging meats, fish, cheese, poultry, nuts and medical pouches

Physical Properties:

	<u>Test Method</u>	<u>Unit of Measure</u>	<u>Typical Values</u>
Color		Clear	
Thickness	Caliper	3.0 mils	
Yield	WEB G 103	in ² /lb	9601
M.V.T.R	ASTM-E96-E	gms/100in ² /24hrs,100°F	0.7
O TR		cc/100in ² /24hrs 73°F, 90%RH	5.5
Gloss 20 degrees			
Seal Side	ASTM-D2457	%	65
Print Side	ASTM-D2457	%	135
Density			0.961

FDA Status

Of the materials used, those that compose the intended product contact surface comply with applicable requirements of the Federal Food, Drug, and Cosmetic Act, as amended.

Users are advised to test the product in advance to make certain it is suitable for their particular production conditions and particular uses. The information and suggested applications set forth herein is furnished free of charge and are based on technical data that SECO Industries believes to be reliable. SECO Industries believes the data values to be typical for the product; however, actual values may vary somewhat from those depicted here. This information is intended for use by persons having technical skill, at their own discretion and risk. Since conditions of use vary and are outside its control, SECO Industries makes NO warranties, express or implied, and assumes no liability in connection with any use of this product.