



SAFE-CELL

- Static Dissipative, non barrier, amine free cellular material
- Meets or exceeds all static dissipative requirements of federal specification PPP-C-795D, Class 2 and MIL-B-81705C, Type 11
- Additive used in the Safe-Cell is amine free and homogeneously blended in the cell and film extrusion process.
- Only standard cushioning material that is Lot Number printed for traceability.

Electrical Properties:

	<u>Test Method</u>	<u>Anti Static Values</u>
Static Decay Rate	5KV-O Volts	<.5 seconds
Surface Resistivity	ASTM-D-257	10(12) ohms/sq.

Physical Properties:

	<u>Test Method</u>	<u>Unit of Measure</u>	<u>Typical Values</u>
Color & Formulation	Both cell and base printed films are static dissipative with no Color(s) added		
Thickness		.002 mil	
Nominal cell/lid thickness		.003 mil	
Nominal printed sheet			
Cell Diameter		3/8 inch	
Cell Height		3/16	
Pattern		200 cell per square foot	

Sizes:

Standard roll 48"x750'. Custom put-ups custom printing and/or company ID is available (call our sales dept. for details)

Heavy Metals and QZone Depleting Substances:

Safe-cell contains NO heavy metals (i.e. lead, cadmium, mercury, & Hexavalent chromium). No blowing agent chemicals are used during cell Formation, only air. This makes Safe-Cell inherently "Ozone friendly".

Recyclability:

Safe-Cell can be recycled as LDPE symbol 4 SPIs voluntary plastic Container coding system. Safe-Cell contains post industrial materials from The recycling of trim in the cell manufacturing process.

Warranty:

All statements, technical information and recommendation concerning Seco Industries – Safe-Cell product are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All data is subject to manufacturing tolerances. All SECO Industries products are sold with the understanding that the purchaser has independently determined the suitability of such products for its purposes. At no time does SECO Industries assume responsibility for claims beyond the replacement value of the invoiced product. No salesman, representative or agent of SECO Industries is authorized to give and guarantee warranty or make any representation contrary to the above. Any modification of the above will be valid only when confirmed in writing by an Executive Officer of Seco Industries.